



塗 装  
内外面 フタル酸樹脂塗料

呼び径	O. D.	G	t	L	W	A	R	重量[kg]
50	60.5±0.5	56 <sup>+0</sup> <sub>-0.7</sub>	6.8	15 <sup>+0.8</sup> <sub>-0</sub>	9 <sup>+0.5</sup> <sub>-0</sub>	51±2	60	0.62
65	76.3±0.5	71.5 <sup>+0</sup> <sub>-0.7</sub>	5.4	15 <sup>+0.8</sup> <sub>-0</sub>	9 <sup>+0.5</sup> <sub>-0</sub>	57±2	95	1.2
80	89.1±0.5	84 <sup>+0</sup> <sub>-0.7</sub>	5.9	15 <sup>+0.8</sup> <sub>-0</sub>	9 <sup>+0.5</sup> <sub>-0</sub>	64±2.5	95	1.5
100	114.3±0.5	109 <sup>+0</sup> <sub>-0.7</sub>	6.7	16 <sup>+0.8</sup> <sub>-0</sub>	9 <sup>+0.5</sup> <sub>-0</sub>	76±3	120	2.51
125	139.8±0.5	134.5 <sup>+0</sup> <sub>-0.7</sub>	7.7	16 <sup>+0.8</sup> <sub>-0</sub>	9 <sup>+0.5</sup> <sub>-0</sub>	83±3	135	4.4
150	165.2±0.5	160 <sup>+0</sup> <sub>-0.7</sub>	8.7	16 <sup>+0.8</sup> <sub>-0</sub>	9 <sup>+0.5</sup> <sub>-0</sub>	89±3	150	5.05

		FCD450-10			
品番	名 称	材 質	個数	備 考	
FITTING 45° ELBOW					
APPROVED BY			DRAWN BY		
CHECKED BY			DESIGNED BY		
SCALE	DATE	DRAWING NO. LE-HP-ELBOW45-01			
THE VICTAULIC COMPANY OF JAPAN LIMITED ENGINEERING DIVISION					