



塗 装
内外面 フタル酸樹脂塗料

呼び径	O. D.	G	t	L	W	A	R	重量[kg]
50	60.5±0.5	56 ⁺⁰ _{-0.7}	4.4	15 ^{+0.8} ₋₀	9 ^{+0.5} ₋₀	83±2	55	1
65	76.3±0.5	71.5 ⁺⁰ _{-0.7}	5.4	15 ^{+0.8} ₋₀	9 ^{+0.5} ₋₀	95±2.5	70	1.5
80	89.1±0.5	84 ⁺⁰ _{-0.7}	5.9	15 ^{+0.8} ₋₀	9 ^{+0.5} ₋₀	108±2.5	80	2.2
100	114.3±0.5	109 ⁺⁰ _{-0.7}	6.7	16 ^{+0.8} ₋₀	9 ^{+0.5} ₋₀	127±3	100	3.6
125	139.8±0.5	134.5 ⁺⁰ _{-0.7}	7.7	16 ^{+0.8} ₋₀	9 ^{+0.5} ₋₀	140±3	110	5.4
150	165.2±0.5	160 ⁺⁰ _{-0.7}	8.7	16 ^{+0.8} ₋₀	9 ^{+0.5} ₋₀	165±3.6	135	8.2
200	216.3±0.5	210.5 ⁺⁰ _{-0.7}	11	19 ^{+1.2} ₋₀	12 ^{+0.5} ₋₀	197±4.1	165	17.7
250	267.4±0.5	261 ⁺⁰ _{-0.7}	12	19 ^{+1.2} ₋₀	12 ^{+0.5} ₋₀	229±4.8	195	27.4

		FCD450-10		
品番	名 称	材 質	個数	備 考
FITTING 90° ELBOW				
APPROVED BY		DRAWN BY		
CHECKED BY		DESIGNED BY		
SCALE	DATE	DRAWING NO. LE-HP-ELBOW90-01		
THE VICTAULIC COMPANY OF JAPAN LIMITED ENGINEERING DIVISION				